

Source: [Legal](#) > [Area of Law - By Topic](#) > [Patent Law](#) > [Patents](#) > [Non-U.S. Patents](#) > [Patent Abstracts of Japan](#) 
Terms: **5110284** ([Edit Search](#))

 Select for FOCUS™ or Delivery



05110284 06326502

COPYRIGHT: 1994, JPO & Japio

PATENT ABSTRACTS OF JAPAN

06326502

◆ [Get Exemplary Drawing](#)

[Access PDF of Official Patent.](#) (Note: Cost incurred in a later step)

The Adobe Acrobat Reader must be installed on your computer to access Official Patent text.
If you do not have this FREE reader, you can download it now from www.adobe.com

November 25, 1994

DISTRIBUTION VARIABLE PHASE SHIFTER

INVENTOR: MITA MASAKI; TAKO NORIYUKI

APPL-NO: 05110284

FILED-DATE: May 12, 1993

ASSIGNEE-AT-ISSUE: SUMITOMO ELECTRIC IND LTD

PUB-TYPE: November 25, 1994 - Un-examined patent application (A)

PUB-COUNTRY: Japan (JP)

IPC-MAIN-CL: H 01P001#18

IPC ADDL CL: H 01P005#12, H 01P005#18, H 01Q003#34, H 01Q011#4

CORE TERMS: h1-h4, plungers, s1-s4, phase, l1-l4, constitution, distributed, synthetic, supplied

ENGLISH-ABST:

PURPOSE: To provide a distribution variable phase shifter which can distribute the electric power and then can continuously vary the phases of distributed signals in a simple and highly reliable constitution.

CONSTITUTION: The input signals are distributed to hybrid circuits H1-H4 by a distributor 1, and the circuits H1-H4 produce two different types of signals having a 90-degree phase difference and supply these signals to the slot line pairs L1-L4. These line pairs L1-L4 are provided with slidable short plungers S1-S4 respectively. The plungers S1-S4 are engaged in common to a control lever 60 which can freely turn around a rotary shaft 65. Then the signals supplied to the line pairs L1-L4 from the circuits H1-H4 are completely reflected by the plungers S1-S4 and then supplied again to the circuits H1-H4. Thus the circuits H1-H4

synthesize these signals together and the synthetic signals are sent to an output terminal B. Then these synthetic signals are turned into the phase signals which are accordant with positions of the plungers S1-S4 respectively.

Source: [Legal](#) > [Area of Law - By Topic](#) > [Patent Law](#) > [Patents](#) > [Non-U.S. Patents](#) > [Patent Abstracts of Japan](#) 

Terms: **5110284** ([Edit Search](#))

View: Full

Date/Time: Wednesday, February 25, 2004 - 11:35 AM EST

[About LexisNexis](#) | [Terms and Conditions](#)

[Copyright](#) © 2004 LexisNexis, a division of Reed Elsevier Inc. All rights reserved.